

Publication number:	DE19800653 (A1)	Also published as:	
Publication date:	1999-07-15		EP1056904 (A2)
Inventor(s):	HUBER ALBERT M [DE]; HUBER JOACHIM CHR [DE]; HUBER WOLFGANG ALEXANDER [DE] +		WO9935331 (A2)
Applicant(s):	HUBER ALBERT M [DE]; HUBER JOACHIM CHR [DE]; HUBER WOLFGANG ALEXANDER [DE] +		WO9935331 (A3)
Classification:		Cited documents:	CA2317528 (A1)
- international:	<b>B04B1/00; D21D5/22; B04B1/00; D21D5/00;</b> (IPC1-7): D21D5/22; B04B1/00; B04B7/08; B04B9/12; B04B11/02; B04B15/06		DE19537567 (A1)
- European:	B04B1/00; D21D5/22		DE3409068 (A1)
Application number:	DE19981000653 19980109		DE8331079U (U1)
Priority number(s):	DE19981000653 19980109		US3791575 (A)
		View all	WO9200810 (A1)

[View INPADOC patent family](#)  
[View list of citing documents](#)  
[Report a data error here](#)

## Abstract of DE 19800653 (A1)

[Translate this text](#)

The invention relates to a solid bowl centrifuge (1) for multiphase mixtures, preferably three-phase mixtures, which is especially meant for fibrous material suspensions used in the paper industry. The solid bowl centrifuge (1) has a housing (2) and a rotor (7) which is provided for separating the multiphase mixture into a light, middle and heavy fraction. At least one orifice (41) situated in the bowl of the rotor (7) is provided for conveying the heavy fraction out. A conveying device (51) is arranged in a chamber (43) between the outer wall (24) of the rotor (7) and the housing (2). Said conveying device conveys a blocking medium into the chamber (43) with at least the pressure prevailing there and in a direction of at least one orifice (41) provided for the heavy fraction.